

FUSION ACTIVE



Fusion Active is designed to fit most work environments where the user does not want to feel restricted in their work. The harness is flexible and adjustable to give the user the best comfort when working at heights.

What makes Fusion Active unique is that it's approved for support and positioning even though it has no support belt.

SEGMENTS

- Pitch roof work
- General industry
 - MEWPs
- Scaffolding

PRODUCT PROPERTIES

Front A-point	Triangle shaped carabiner (carabiner 9656) in textile loops
Chest buckles	Triangle shaped carabiner of aluminum (carabiner 9656)
Back A-point	Plastic overmolded steel ring self luminous PVC 53 mm
Side D-rings	Galvanized steel 50 mm >30kN for positioning
Side adjuster	Heat treated steel saltspray tested 74 hours >18kN
Leg buckles	Quickbuckles in steel with stainless components Strength >20kN
Padding material	Breathable 3-D mesh
Adjustable under load	Yes
Fall indicator	No
Maximum number of users	1
Maximum load (kg)	140.0
Minimum working temperature (c)	-40.0
Maximum working temperature (c)	100.0
Minimum breaking strength - MBS (kN)	15.0
Material	Polyester
Extra functions	Support belt function without support belt

CLASSIFICATION

PPE-category	Category 3
EN-standard	EN 361 : 2004, CNB/P11.043 Rev2

ANNUAL INSPECTION

Annual inspection	Yes, every 12 months
Life span	10 + 2 years. Product lifecycle 10 years + 2 years stock keeping
Warranty	2+1 year when registered in Inspector
Identification	Serial number
RFID	Yes

DOCUMENTS

Declaration of Conformity	Yes
---------------------------	-----

SKU: 01220008 | Category: [Fall Limit](#) |

VARIATIONS





Image	SKU	Price	Description	Size	Colour
	012200081			S/M	Black/Grey
	012200083			s-m-long	Black/Grey

Image	SKU	Price	Description	Size	Colour
	012200085			L/XL	Black/Grey
	012200087			XXL	Black/Grey

ADDITIONAL INFORMATION

Size	L/XL, s-m-long, S/M, XXL
Colour	Black/Grey

PRODUCT FILES

No files for this product.

