

HAIX AIRPOWER XR91 HI1 F1PA RESCUE BOOT



Haix Airpower XR91 is a protective boot in leather that is fire-rated with an outsole in PU and rubber.

- Equipped with a patented cord and locking system, called FL-Fit System
 - Heat-resistant and cold-insulated rubber sole
 - Composite toe cap and steel spike protection
- Sun Reflect: Reduces the heat build-up of sunlight by the sunlight being reflected by the leather

Procurator Nail Steel

Procurator Sole Heat resistant

Procurator Toe Wear

Procurator Toecap Composite

Procurator Water Repellant

Crosstech

SKU: 20812 | **Categories:** [Boots](#), [Fire Fighter](#), [Safety Shoes](#), [Shoes](#) |

VARIATIONS

Image	SKU	Price	Description	Size	Colour
	2081274			37	Black
	2081275			38	Black





Image	SKU	Price	Description	Size	Colour
	2081276			39	Black
	2081277			40	Black
	2081278			41	Black
	2081279			42	Black

Image	SKU	Price	Description	Size	Colour
	2081280			43	Black
	2081281			44	Black
	2081282			45	Black
	2081283			46	Black

Image	SKU	Price	Description	Size	Colour
	2081284			47	Black
	2081285			48	Black
	2081286			50	Black

PRODUCT DESCRIPTION

CE 0197 EN 15090:2012 HI1 CI T SRC - Type F1PA

Leather thickness 2,0 - 2,2 mm, waterproof, breathable, bacteria and chemical resistant with CROSSTECH® , leg height 19,5 cm, antistatic, sole 012

Upper Material

Waterproof leather, hydrophobic, breathable (5,0 mg/cm²/h), 2.0 - 2.2 mm thick.

Inner lining

CROSSTECH® Laminat Technology; 3-layer CROSSTECH® laminate, watertight and breathable. Abrasion-resistant lining with optimized climate comfort for all seasons, espec. for flexible alternating inside and outside use. Superior penetration resistance against blood and body fluids (protection against blood borne bacteria and virus). Increased chemical protection.

Insert

Comfortable, cushioning, moisture repellent, anti-bacterial. Separate heel shape for good cushioning and foot insertion. "AIRFLOW" channels. „Perfect-Fit“ mark for an optimal verification of the correct shoe size.

HAIX® Composite Toe Cap

Anatomically formed and ultralight protective toe cap made of fiber-reinforced plastic for highest safety requirements.

Non-woven insole

Non-woven insole absorbs sweat and moisture.

Protective Throughsole

Flexible, lightweight and protective metal throughsole.

Sole

Rubber sole with robust street tread, superior bending comfort, highly wear resistant, non-slip traction - even in cold weather. The low-weight PU, impact-absorbing wedge ensures outstanding walking characteristics. Very good insulation from heat and cold. The sole is resistant against heat, flames, oil and gasoline, non-marking. Compliant with EN ISO 20345:2012 / EN 15090:2012.

HAIX® AS System

Optimal support and shock absorption in the arch provided by an anatomically formed last. Improved heel and arch design provides support while securing the foot, allowing for increased comfort and range of motion in the spacious toe area.

HAIX® TPU cap

Extra protection and abrasion resistance due to external tpu cap.

HAIX® Climate System

The HAIX Climate system uses the pumping movement, which permits air circulation with every step - warm air is released and fresh air comes in through the vent holes at the top of the boot.

Sun Reflect

Reduces the heating effect of the upper leather by direct sunlight. Sunlight is reflected by the leather, keeping the leather and the feet cooler.

HAIX® Vario Wide Fit System

The width of the shoe can be individually adjusted by 3 different insoles. The shoe is supplied with a red insole (medium). A yellow insole (wide) and blue insole (narrow) can be ordered separately.

Others

Perfect boot for technical operations, day duty, fighting forest fires and rescue service compliant with fire fighting EN and BS standards, abrasion resistant toe cap, reflective strips, HAIX® Fast Lacing Fit System, pull-on loops, metatarsal protector

ADDITIONAL INFORMATION

Size 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 50

Colour Black

PRODUCT FILES

No files for this product.

